

DGR25 Multi-Conductor - Category 5 Nonbonded-Pair Armored Cable

For more Information
please call

1-800-Belden1

**Description:**

24 AWG solid bare copper, polyolefin insulation, twenty-five twisted pairs, Alvyon (Alpast) sheath, Overall PVC jacket.

Usage (Overall)

Suitable Applications:

Multi-pair backbone cables for high-speed applications.

Physical Characteristics (Overall)**Conductor**

AWG:

# Pairs	AWG	Stranding	Conductor Material
25	24	Solid	BC - Bare Copper

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter:

0.685 in.

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue
2	White/Orange
3	White/Green
4	White/Brown
5	White/Slate
6	Red/Blue
7	Red/Orange
8	Red/Green
9	Red/Brown
10	Red/Slate
11	Black/Blue
12	Black/Orange
13	Black/Green
14	Black/Brown
15	Black/Slate
16	Yellow/Blue
17	Yellow/Orange
18	Yellow/Green
19	Yellow/Brown
20	Yellow/Slate
21	Violet/Blue
22	Violet/Orange

DGR25 Multi-Conductor - Category 5 Nonbonded-Pair Armored Cable

23	Violet/Green
24	Violet/Brown
25	Violet/Slate

Mechanical Characteristics (Overall)

Operating Temperature Range:	-30°C To +60°C
UL Temperature Rating:	60°C
Bulk Cable Weight:	281 lbs/1000 ft.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMR
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	08/19/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	Meets or exceeds Category 5 transmission characteristics including the PowerSum Near End Crosstalk requirements from ANSI/TIA/EIA-568-A

Flame Test

UL Flame Test:	UL1666 Riser
C(UL) Flame Test:	FT4

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Maximum Capacitance Unbalance (pF/100 m):	328
---	-----

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
9.380

Electrical Characteristics-Premise (Overall)**Premise Cable Electricals:**

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. PSNEXT (dB)	Min. SRL (dB)	Fitted Imp. (Ohms)
.772	1.800	64		102 +/- 15%
1	2.100	62	23	100 +/- 15%
4	4.300	53	23	100 +/- 15%
8	5.900	48	23	100 +/- 15%
10	6.600	47	23	100 +/- 15%
16	8.200	44	23	100 +/- 15%
20	9.200	42	23	100 +/- 15%
25	10.500	41	22	100 +/- 15%
31.25	11.800	40	21	100 +/- 15%
62.5	17.100	35	18	100 +/- 15%
100	22.000	32	16	100 +/- 15%

Notes (Overall)

Notes: Jacket sequentially printed with dual footage and meter markings.

DGR25 Multi-Conductor - Category 5 Nonbonded-Pair Armored Cable**Reference (Overall)****Previous Part Number:** 25500028**Related Documents:**

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
DGR25 008CUT	1 FT	0.000	GRAY		CAT5 25PR ARMOR CMR CUT

Revision Number: 0 Revision Date: 04-24-2009

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.