


1015A Multi-Conductor - Thermocouple



**Obsolete
Call
1-800-BELDEN1**

For more Information
please call

1-800-Belden1

Description:

20 AWG pairs, solid conductors, chromel & alumel, individually shielded, overall 100% Beldfoil® shield, PVC insulation, PVC jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
8	20	Solid	Chromel
8	20	Solid	Alumel
	22	7x30	BC - Bare Copper

Insulation**Insulation Material:**

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.016

Inner Shield**Inner Shield Material:**

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
22

Inner Shield Drain Wire Stranding: 7x30

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Outer Shield**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling**Overall Cabling Lay Length & Direction:**

Length (in.)
8.5

Overall Nominal Diameter: 0.692 in.

Pair**Pair Lay Length & Direction:**

Lay Length (in.)	Twists/ft. (twist/ft)
2.500	4.800

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +105°C

1015A Multi-Conductor - Thermocouple

Non-UL Temperature Rating:	105°C
Bulk Cable Weight:	301 lbs/1000 ft.
Max. Recommended Pulling Tension:	566 lbs.
Min. Bend Radius (Install)/Minor Axis:	7 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

CEC/C(UL) Specification:	CMG
CSA Specification:	FT4
IEEE Specification:	1202

Flame Test

UL Flame Test:	UL 1685 FT4 Loading
----------------	---------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Surface Printing (Overall)

Surface Printing:	BELDEN 1015A E34972 16PR20 1C22 THCPL EXTN KX SHIELDED (UL) CMG 105C OR PLTC OR ITC SUN RES DIR BUR OR AWM 2464 80C 300V OR C(UL) CMG ---- FT4 IEEE1202 (2 FT, 7 DIGIT SEQUENTIAL NUMBER) FEET
-------------------	---

Electrical Characteristics (Overall)**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

6.8

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C:	10.600 Ohm/1000 ft
---	--------------------

Notes (Overall)

Notes: Chromel & Alumel = "Chromel and Alumel are Hoskins Manufacturing Company trademarks."

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 1 Revision Date: 04-18-2008

© 2008 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.