



For more Information
please call

1-800-Belden1



Description:

(2) Coax : 25 AWG (7x30) BC, GIFPE insul., Dufoil® plus TC braid (95% cov.), PVC inner jacket. (3) Pairs: 22 AWG TC, PP insul., Beldfoil® with drain, PVC Jackets. Color Coded Jackets. Cabled. Overall flexible PVC jacket.

Usage (Overall)

Suitable Applications: Electronic News Gathering (ENG), Electronic Field Production (EFP), Analog Audio + Digital Video Composite Applications, 2 V + 3A

Coax

Physical Characteristics

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
2	25	7x33	BC - Bare Copper	0.021

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FPE - Foam Polyethylene	0.100

Inner Shield

Inner Shield Material:

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	% Coverage (%)
1	Dufoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	95

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	0.160

Inner Jacket Color Code Chart:

Number	Color
1	Red
2	Black

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

EU CE Mark: No

RG Type: 59/U

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
17.300

Nominal Velocity of Propagation:

VP (%)

78.000

Nominal Delay:

Delay (ns/ft)

1.300

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

30.200

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

5.900

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.450
5.000	1.100
10.000	1.500
50.000	3.200
100.000	4.300
300.000	10.600
500.000	13.800

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
3	22	7x30	Tc - Tinned Copper	0.030

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PP - Polypropylene	0.046

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG	Stranding	Dia. (in.)	Conductor Material
22	7x30	0.030	TC - Tinned Copper

Inner Jacket

Inner Jacket Color Code Chart:

Number	Color
1	Black and Red
2	Black and Red
3	Black and Red

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)

50

Nom. Inductance:

Inductance (µH/ft)

0.170

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

32.000

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
58.000

Nominal Velocity of Propagation:

VP (%)
66.000

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
11.300

Max. Operating Voltage - Non-UL:

Voltage
150 V RMS

Multi Conductor

Physical Characteristics

Conductor

AWG:

Triads
1

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	0.125

Inner Jacket Color Code Chart:

Number	Color
1	Brown
2	Red
3	Orange

Physical Characteristics (Overall)

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 0.492 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

UL Temperature Rating: 60°C

Bulk Cable Weight: 103 lbs/1000 ft.

Max. Recommended Pulling Tension: 135 lbs.

Min. Bend Radius (Install)/Minor Axis: 5 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

1263B Composite - Cables for TV Cameras and CCTV

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Max. Operating Voltage - UL:

Voltage

30 V RMS

Notes (Overall)

Notes: Round Construction

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1263B J5C1000	1,000 FT	114.000 LB	BLACK, VIVID MATTE	C	2 #25 COAX 3 PR #22 PP PVC PVC
1263B J5C500	500 FT	60.500 LB	BLACK, VIVID MATTE	C	2 #25 COAX 3 PR #22 PP PVC PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 0 Revision Date: 02-20-2009

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.