

## 1694D Coax - Dual RG-6/U Type Precision Low Loss Serial Digital Video coax



For more Information  
please call

1-800-Belden1



### Description:

Dual RG-6/U type, (2) 18 AWG solid .040" bare copper conductors, gas-injected foam HDPE insulation, Duofoil® plus tinned copper braid shield (95% coverage), inner PVC jackets, overall PVC jacket.

### Usage (Overall)

**Suitable Applications:** Video Mult.

### Physical Characteristics (Overall)

#### Conductor

**AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
2	18	Solid	BC - Bare Copper	0.040

#### Insulation

**Insulation Material:**

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	.180

#### Inner Shield

**Inner Shield Material:**

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

#### Inner Jacket

**Inner Jacket Material:**

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.275

**Inner Jacket Color Code Chart:**

Number	Color
1	Red
2	Green

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

**Overall Nominal Diameter:** 0.344 x 0.618 in.

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -40°C To +75°C

**UL Temperature Rating:** 60°C

**Non-UL Temperature Rating:** 75°C

**Bulk Cable Weight:** 109 lbs/1000 ft.

**Max. Recommended Pulling Tension:** 177 lbs.

## 1694D Coax - Dual RG-6/U Type Precision Low Loss Serial Digital Video coax

Min. Bend Radius (Install)/Minor Axis: 3.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/09/2010
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
RG Type:	6/U

#### Flame Test

UL Flame Test: UL1666 Vertical Shaft

#### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

#### Plenum/Non-Plenum

Plenum (Y/N): No

### Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

Impedance (Ohm)  
75

#### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)  
16.2

#### Nominal Velocity of Propagation:

VP (%)  
82

#### Nominal Delay:

Delay (ns/ft)  
1.24

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)  
6.4

#### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)  
2.800

#### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.240
3.580	0.440
5.000	0.520
7.000	0.610
10.000	0.710
67.500	1.650
71.500	1.690
88.500	1.860

## 1694D Coax - Dual RG-6/U Type Precision Low Loss Serial Digital Video coax

100.000	1.950
135.000	2.240
143.000	2.300
180.000	2.570
270.000	3.170
360.000	3.690
540.000	4.600
720.000	5.380
750.000	5.500
1000.000	6.420
1500.000	7.990
2000.000	9.370
2250.000	10.010
3000.000	11.780

### Max. Operating Voltage - UL:

<b>Voltage</b>
300 V RMS

**Other Electrical Characteristic 1:** Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.

**Other Electrical Characteristic 2:** Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

### Minimum Structural Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. SRL (dB)
5	580	23
580	680	15
680	850	23
850	3000	15

### Sweep Test

**Sweep Testing:** Sweep tested 5 MHz to 3 GHz.

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1694D 0101000	1,000 FT	131.000 LB	BLACK	C	2 #18 PE SH PVC FRPVC PARA PVC
1694D 010500	500 FT	66.000 LB	BLACK		2 #18 PE SH PVC FRPVC PARA PVC

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 03-24-2011

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.