

**Picture
Not Available**

For more Information
please call

1-800-Belden1

Description

RG-59/U Type Plenum RGB coaxial cable, 4 coaxes. Each coax 22 AWG (7x30) bare copper, Foam FEP core, Duofoil® + 95% tinned copper braid, fluorocopolymer jacket; overall Beldfoil® and Flamarrest® jacket.

Physical Characteristics (Overall):

Conductor:

AWG

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
4	22	7x30	BC - Bare Copper	0.030

Total Number of Conductors 4

Insulation:

Insulation Material

Ins Trade Name	Ins Material	Dia. (in.)
Teflon®	FFEP - Foam Fluorinated Ethylene Propylene	0.135

Inner Shield:

Inner Shield Material

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	% Coverage (%)
1	Duofoil®	Tape		100
2		Braid	Tinned Copper Braid	95

Inner Jacket:

Inner Jacket Material

Inner Jacket Material	Nom. Dia. (in.)
Fluoropolymer	0.200

Inner Jacket Color Code Chart

Number	Color
1	Red
2	Green
3	Blue
4	White

Outer Shield:

Outer Shield Material

Outer Shield Trade Name	Type	Outer Shield Material	% Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC - Tinned Copper

Outer Jacket:

Outer Jacket Material

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	FA - Flamarrest®

Overall Cabling:

Overall Nominal Diameter: 0.527 in.

Mechanical Characteristics (Overall):

Operating Temperature Range	-0°C To +60°C
Non-UL Temperature Rating	60°C
Bulk Cable Weight:	118 lbs/1000 ft.
Max. Recommended Pulling Tension:	260 lbs.
Min. Bend Radius (Install):	5 in.

Applicable Specifications and Agency Compliance (Overall):

ENGLISH MEASUREMENT VERSION

1825A Coax - RGB and SVHS Cable**Applicable Standards:**

NEC/(UL) Specification CMP

RG Type 59/U

Flame Test:

UL Flame Test 910 Steiner Tunnel

Plenum/Non-Plenum:

Plenum (Y/N) Y

Electrical Characteristics (Overall):

Nom. Characteristic Impedance

Impedance (Ohm)
75

Nom. Capacitance Conductor to Shield

Capacitance (pF/ft)
17.300

Nominal Velocity of Propagation

VP (%)
81

Nominal Delay

Delay (ns/ft)
1.260

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft)
15.300

Nom. Inner Shield DC Resistance

Description	DCR @ 20°C (Ohm/1000 ft)
Each Coax	2.500

Nom. Attenuation

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100 ft.)
Nominal Attenuation	1.000			0.300
	5.000			0.600
	10.000			0.800
	30.000			1.500
	50.000			1.900
	100.000			2.900
	200.000			4.300
	400.000			6.600
	700.000			9.400
	900.000			11.100
	1000.000			11.900

Max. Operating Voltage - UL

Voltage
300 V RMS

Minimum Structural Return Loss

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. SRL (dB)
Minimum Structural Return Loss		10.000	40.000	25.000

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/1000 ft)
11.100

Revision Number: 1 Revision Date: 05-14-2007

 © 2007 Belden, Inc.
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect,

incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS). EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.