


26522 Triad - 300V ACIC Armored Cable

For more Information
please call

1-800-Belden1

**Description:**

18 AWG triads stranded (7x26) tinned copper conductors, individual Beldfoil plus a polyester isolation tape, PVC insulation, PVC inner jacket, overall Beldfoil shield (100% coverage), drain wires, interlocked armor, PVC outer jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Triads	AWG	Stranding	Conductor Material
1	18	7x26	TC - Tinned Copper

Insulation**Insulation Material:**

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.025

Inner Shield**Inner Shield Color Code Chart:**

Number	Color
1	Black & White & Red

Inner Jacket**Inner Jacket Material:**

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.33

Outer Shield**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord: Yes

Outer Jacket over Armor (y/n): Y

Armor

Armor Type: Interlocked

Armor Material: Steel

Diameter over Armor: .51

Overall Cable

Overall Nominal Diameter: 0.610 in.

Mechanical Characteristics (Overall)

Installation Temperature Range:	-25°C To +105°C
Wet Temperature Range:	-40°C To +75°C
Dry Temperature Range:	-40°C To +105°C
Non-UL Temperature Rating:	105°C
Bulk Cable Weight:	275 lbs/1000 ft.
Max. Recommended Pulling Tension:	80 lbs.
Min. Bend Radius (Install)/Minor Axis:	7.300 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CSA Specification:	C22.2#239, Type ACIC, C22.2#174, HLBCD, C22.2#0.3, Clause 4.31 Low Acid Test
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

C(UL) Flame Test:	FT4
-------------------	-----

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.8

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
10

Max. Operating Voltage - Non-UL:

Voltage
300

Max. Operating Voltage - Other:

Voltage	Description
300	CSA ACIC

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

26522 Triad - 300V ACIC Armored Cable

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.