Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION

26529 Triad - 300V ACIC Armored Cable



For more Information
please call

1-800-Belden1

Description:

18 AWG triads stranded (7x26) tinned copper conductors, individual Beldfoil plus a polyester isolation tape, PVC insulation, PVC inner jacket, overall Beldfoil shield (100% coverage), drain wires, interlocked armor, PVC outer jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Triads	AWG	Stranding	Conductor Material
24	18	7x26	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.025

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
22

Inner Shield Drain Wire Stranding: 7x30

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Inner Shield Color Code Chart:

Number	Color
1	Black & White & Red and Numbered 1
2	Black & White & Red and Numbered 2
3	Black & White & Red and Numbered 3
4	Black & White & Red and Numbered 4
5	Black & White & Red and Numbered 5
6	Black & White & Red and Numbered 6
7	Black & White & Red and Numbered 7
8	Black & White & Red and Numbered 8
9	Black & White & Red and Numbered 9
10	Black & White & Red and Numbered 10
11	Black & White & Red and Numbered 11
12	Black & White & Red and Numbered 12
13	Black & White & Red and Numbered 13
14	Black & White & Red and Numbered 14
15	Black & White & Red and Numbered 15
16	Black & White & Red and Numbered 16
17	Black & White & Red and Numbered 17
18	Black & White & Red and Numbered 18
19	Black & White & Red and Numbered 19
20	Black & White & Red and Numbered 20
21	Black & White & Red and Numbered 21

22	Black & White & Red and Numbered 22
23	Black & White & Red and Numbered 23
24	Black & White & Red and Numbered 24

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	1.37

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
18	7x26	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord:	Yes
Outer Jacket over Armor (y/n):	Y

Armor

Armor Type:	Interlocked
Armor Material:	Steel

Overall Cable

Overall Nominal Diameter:	1.800 in.

Mechanical Characteristics (Overall)

Installation Temperature Range:	-25°C To +105°C
Wet Temperature Range:	-40°C To +75°C
Dry Temperature Range:	-40°C To +105°C
Non-UL Temperature Rating:	105°C
Bulk Cable Weight:	1775 lbs/1000 ft.
Max. Recommended Pulling Tension:	1942 lbs.
Min. Bend Radius (Install)/Minor Axis:	21.600 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CSA Specification:	C22.2#239, Type ACIC, C22.2#174, HLBCD, C22.2#0.3, Clause 4.31 Low Acid Test
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

C(UL) Flame Test:	FT4

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No

Electrical Characteristics (Overall)

Max. Operating Voltage - Other:

Voltage	Description
300	CSA ACIC

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.