

27862 Multi-Conductor - 600V Teck-Style® Cables



For more Information
please call

1-800-Belden1

**Description:**

12 AWG stranded (7x20) bare copper conductors, 12 AWG bare copper ground wire, cross-linked polyethylene insulation, PVC inner jacket, aluminum armor, PVC outer jacket.

Physical Characteristics (Overall)**Conductor**

AWG:

# Conductors	AWG	Stranding	Conductor Material
15	12	7x20	BC - Bare Copper

Ground Wire

Ground Wire (Y/N):	Y
Ground Wire AWG:	12
Ground Wire Stranding:	7x20
Ground Wire Conductor Material:	BC - Bare Copper

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
XLPE - Cross Linked Polyethylene	.030

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.87

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket over Armor (y/n):	Y
--------------------------------	---

Outer Jacket over Armor

Outer Jacket Material over Armor (y/n):	PVC
---	-----

Armor

Armor Type:	Interlocked
Armor Material:	Aluminum
Diameter over Armor:	1.13

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red
3	Blue
4	Orange
5	Yellow

27862 Multi-Conductor - 600V Teck-Style® Cables

6	Brown
7	Red/Black
8	Blue/Black
9	Orange/Black
10	Yellow/Black
11	Brown/Black
12	Black/Red
13	Blue/Red
14	Orange/Red
15	Yellow/Red

Overall Nominal Diameter: 1.250 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +90°C
Wet Temperature Range:	-40°C To +90°C
Dry Temperature Range:	-40°C To +90°C
Bulk Cable Weight:	823 lbs/1000 ft.
Max. Recommended Pulling Tension:	718 lbs.
Min. Bend Radius (Install)/Minor Axis:	15 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	MC, XHHW-2 Singles, UL1569, UL1277
CSA Specification:	C22.2#131, HAZ LOC, C22.2#0.3 Clause 4.31 Low Acid Test
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/13/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	VW-1 Singles, UL1685 UL Loading
CSA Flame Test:	FT4
IEEE Flame Test:	IEEE 1202
Other Flame Test:	ICEA T-29-520

Suitability

Suitability - Burial:	Yes
Sunlight Resistance:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

1.65

Max. Operating Voltage - UL:

Voltage

600 V RMS

27862 Multi-Conductor - 600V Teck-Style® Cables

Max. Recommended Current:

Current
10 Amps per conductor @ 25°C

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.