

35422 Hook-up/Lead - UL AWM Style 3436 and 3321 - XL-DUR®



**Obsolete
Call
1-800-BELDEN1**

For more Information
please call

1-800-Belden1

Description:

This cross-linked polyethylene lead wire is available for higher temperature applications. It is UL recognized to 600V, 150°C. As with other XLPE polyethylene lead wire, it has excellent heat aging characteristics, electrical and physical properties.

Physical Characteristics (Overall)**Conductor****AWG:**

# Conductors	AWG	Stranding	Conductor Material
1	22	7x30	TC - Tinned Copper

Insulation**Insulation Material:**

Insulation Material	Wall Thickness (in.)
XLPE - Cross Linked Polyethylene	.030

Overall Insulation**Overall Cabling**

Overall Nominal Diameter: 0.093 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

UL AWM Style:	3436, 3321
UL Rating:	600 V, 150°C
CSA Rating:	600 V, 125°C, 150°C
CSA Type:	CL1251, AWM

Plenum/Non-Plenum

Plenum (Y/N): No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 1 Revision Date: 05-14-2007

© 2008 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.