

4812 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable



For more Information
please call

1-800-Belden1

**Description:**

23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Twisted Pairs, X Spline Center Member, Rip Cord, PVC Jacket.

Usage (Overall)**Suitable Applications:**

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG
ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video,
AES/EBU Digital Audio, AES51, RS-422, Noisy Environments

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Insulation**Insulation Material:**

Insulation Material
PO - Polyolefin

Outer Shield**Outer Shield Material:**

Outer Shield Material
Unshielded

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.255

Outer Jacket Ripcord:

Yes

Overall Cable**Overall Cabling Separator Material:**

X-Spline Center Member

Overall Nominal Diameter:

0.255 in.

Pair**Pair Color Code Chart:**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)**Storage Temperature Range:**

-20°C To +75°C

Installation Temperature Range:

+5°C To +50°C

4812 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable

Operating Temperature Range:	-20°C To +60°C
Bulk Cable Weight:	31 lbs/1000 ft.
Max. Recommended Pulling Tension:	45 lbs.
Min. Bend Radius (Install)/Minor Axis:	1.500 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMR
Other Standards:	ISO/IEC 11801 ed 2.1 (2008) Class E
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6 - TIA 568.C.2
Other Specification:	UL verified to Category 6

Applicable Patents:

Country	Patent
US	6074503
US	7663061
US	7977575

Flame Test

UL Flame Test:	UL1666 Vertical Riser
C(UL) Flame Test:	FT4
CSA Flame Test:	FT4

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Sunlight Resistance:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	4813

Electrical Characteristics (Overall)**Nom. Mutual Capacitance:**

Capacitance (pF/ft)
15.500

Maximum Capacitance Unbalance (pF/100 m):	90
---	----

Nominal Velocity of Propagation:

VP (%)
68.000

Maximum Delay:

Delay (ns/100 m)

4812 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable

538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)
25.000

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
6.600

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
0.772	1.700	82	80	80.3	78.3	
1	1.800	80.3	78.3	78.5	76.5	20.000
4	3.400	71.3	69.3	67.9	65.9	23.000
8	4.800	66.8	64.8	62	60	24.500
10	5.300	65.3	63.3	60	58	25.000
16	6.800	62.2	60.2	55.5	53.5	25.000
20	7.600	60.8	58.8	53.2	51.2	25.000
25	8.500	59.3	57.3	50.8	48.8	25.000
31.25	9.600	57.9	55.9	48.3	46.3	24.200
62.5	13.800	53.4	51.4	39.6	37.6	22.900
100	17.800	50.3	48.3	32.5	30.5	22.100
155	22.700	47.4	45.4	24.8	22.8	21.300
200	26.200	45.8	43.8	19.6	17.6	20.900
250	29.700	44.3	42.3	14.6	12.6	20.400
300	33.000	43.1	41.1	10.2	8.2	20.100
350	36.000	42.1	40.1	6.1	4.1	19.800
400	39.000	41.3	39.3	2.3	0.3	19.600
450	41.800	40.5	38.5	-1.3	-3.3	19.400
500	44.500	39.8	37.8	-4.6	-6.6	19.200
550	47.100	39.2	37.2	-7.9	-9.9	19.000
600	49.600	38.6	36.6	-11.0	-13.0	18.900

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
0.772		102 ± 15	77	74
1	100 ± 15	100 ± 15	74.8	71.8
4	100 ± 15	100 ± 15	62.8	59.8
8	100 ± 15	100 ± 15	56.7	53.7
10	100 ± 15	100 ± 15	54.8	51.8
16	100 ± 15	100 ± 15	50.7	47.7
20	100 ± 15	100 ± 15	48.8	45.8
25	100 ± 15	100 ± 15	46.8	43.8
31.25	100 ± 15	100 ± 15	44.9	41.9
62.5	100 ± 15	100 ± 15	38.9	35.9
100	100 ± 15	100 ± 15	34.8	31.8
155	100 ± 15	100 ± 15	31	28
200	100 ± 15	100 ± 15	28.8	25.8
250	100 ± 22	100 ± 15	26.8	23.8
300	100 ± 22	100 ± 15	25.3	22.3
350	100 ± 22	100 ± 15	23.9	20.9
400	100 ± 22	100 ± 15	22.8	19.8
450			21.7	18.7

4812 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cable

500			20.8	17.8
550			20	17
600			19.2	16.2

Notes (Overall)

Notes: Belden IBDN. Jacket sequentially marked at 2 ft./1m intervals. Values above 400 MHz are for Engineering Information Only.
 Third party verified to ANSI/TIA-568-C.2, Category 6.

Reference (Overall)

Previous Part Number: 24586685, 24586685+US, 24586785, 24586785+US, 25086885, 25086885+US, 24586985, 24586985+US, 24586956, 24586956+US, 24586915, 24586915+US, 24586185, 24586385, 24586385+US, 24586315, 24586315+US, 24586451+US

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
4812 0021000	1,000 FT	31.000 LB	RED		CAT6E+ 4PR U/UTP CMR REEL
4812 0041000	1,000 FT	31.000 LB	YELLOW		CAT6E+ 4PR U/UTP CMR REEL
4812 0051000	1,000 FT	31.000 LB	GREEN, DARK		CAT6E+ 4PR U/UTP CMR REEL
4812 006A1000	1,000 FT	31.000 LB	BLUE, LIGHT		CAT6E+ 4PR U/UTP CMR RIB
4812 0061000	1,000 FT	31.000 LB	BLUE, LIGHT		CAT6E+ 4PR U/UTP CMR REEL
4812 0062500	2,500 FT	82.500 LB	BLUE, LIGHT		CAT6E+ 4PR U/UTP CMR REEL
4812 0081000	1,000 FT	31.000 LB	GRAY		CAT6E+ 4PR U/UTP CMR REEL
4812 009A1000	1,000 FT	31.000 LB	WHITE		CAT6E+ 4PR U/UTP CMR RIB
4812 0091000	1,000 FT	31.000 LB	WHITE		CAT6E+ 4PR U/UTP CMR REEL
4812 0103000	3,000 FT	102.000 LB	BLACK		CAT6E+ 4PR U/UTP CMR REEL

Revision Number: 8 Revision Date: 10-26-2011

© 2012 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.