


49440 Molded Cable Assemblies - Modular Keyboard Assembly



For more Information
please call

1-800-Belden1



Description:

4-position modular retractile, used to rapidly interconnect electronic computers and business machines, polypropylene insulation, unshielded, polyurethane jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
4	26	19x38	TC - Tinned Copper	.51

Number of Pins: 4

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PP - Polypropylene	0.006

Connector Characteristics

Connector Characteristics - First End # of Connector Contacts/positions: 4

Connector Characteristics - First End Connector Type: Modular

Connector Characteristics - Second End # of Connector Contacts/positions: 4

Connector Characteristics - Second End Connector Type: Modular

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PUR - Polyurethane	0.03

Overall Cable

Overall Nominal Diameter: 0.093 x 0.198 in.

Assembly Dimensional

Assembly Dimensional For Retractable Coil Body Length (extended): 67.5

Assembly Dimensional for Retractable Coil Body Length (relaxed): 15

Tail Length

1st End Tail Length: 1.5 +/- .5

2nd End Tail Length: 1.5 +/- .5

Wiring

49440 Molded Cable Assemblies - Modular Keyboard Assembly

Wiring: Cross Wired. Pin 1 on end 1 to pin 4 on end 2, pin 2 on end 1 to pin 3 on end 2, pin 3 on end 1 to pin 2 on end 2 and pin 4 on end 1 to pin 1 on end 2

Mechanical Characteristics (Overall)

UL Temperature Rating: 60°C (UL AWM Style 20197)

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

AWM Specification: UL Style 20197 (30 V 60°C) (cable only)

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Max. Operating Voltage - UL:

Voltage

30V (UL AWM Style 20197)

Notes (Overall)

Notes: Positive locking latch prevents connector from vibrating loose. Polarized connector prevents improper insertion. No tools required for installation.

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
49440 010S2	1 EA	0.260 LB	BLACK		4 POS MOD RET CABLE RI47849

Revision Number: 1 Revision Date: 09-19-2008

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.