Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION

581967 Multi-Conductor - Spec 19-4 Self-supporting Signal and Communications Cable

Picture Not Available

For more Information please call

1-800-Belden1

Description:

16 AWG stranded (7x24) bare copper conductors, HDPE insulation, corrugated copper tape shield, steel messenger, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
3	16	7x24	BC - Bare Copper

Insulation

Insulation Material:

Insulation Material
HDPE - High Density Polyethylene

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Tape	Corrugated Copper Tape	100

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.060

Messenger

Messenger Diameter:	0.250 in.
Messenger Material:	Steel

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	White & Blue
2	White & Orange
3	White & Green

Overall Nominal Diameter:	0.626 x 1.096 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-30°C To +80°C
Bulk Cable Weight:	340 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	11.100 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/1/2005

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
IMSA Specification:	19-4

Suitability

Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
4.2

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc

Revision Number: 1 Revision Date: 06-28-2011

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.