

# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 601PTZ Composite - For PTZ Cameras: CCTV + Control + Power



For more Information  
please call

1-800-Belden1



### Description:

(1) coax-20 AWG solid BC cond., gas-injected foam HDPE insul., 95% BC braid shld., cabled with (1) pair-22 AWG stranded (7x30) solid BC cond., PO insul., Beldfoil® shld., cabled with (2) cond.-18 AWG (7x26) BC cond., PVC insul., with Flamarrest® jkts.

### Coax

#### Physical Characteristics

##### Conductor

AWG:

#	Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1		20	Solid	BC - Bare Copper	0.032

##### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FPFA - Foam Perfluoroalkoxy	0.133

##### Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

##### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.193

Outer Jacket Color Code Chart:

Number	Color
Video	Black

### Applicable Specifications and Agency Compliance

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU CE Mark: Yes

RG Type: 59/U

#### Flame Test

UL Flame Test: NFPA 262

#### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

#### Nom. Characteristic Impedance:

Impedance (Ohm)

Distributed By:



Page 1 of 5

1-800-527-0010

01-06-2012

# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 601PTZ Composite - For PTZ Cameras: CCTV + Control + Power

75

### Nom. Inductance:

Inductance ( $\mu$ H/ft)
0.097

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
16.100

### Nominal Velocity of Propagation:

VP (%)
84.000

### Nominal Delay:

Delay (ns/ft)
1.210

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
10.000

### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
2.500

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.290
5.000	0.700
10.000	1.100
50.000	1.800
100.000	2.700
200.000	3.900
400.000	5.900
700.000	8.500
900.000	10.000
1000.000	10.700

Max. Operating Voltage - UL:

300 V RMS

## Twisted Pair

### Physical Characteristics

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	22	7x30	BC - Bare Copper	0.030

#### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FEP - Fluorinated Ethylene Propylene	0.042

#### Twisted Pair Color Code Chart:

Number	Color
1	Blue and White/Blue

#### Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC - Tinned Copper

Distributed By:



Page 2 of 5

1-800-527-0010

01-06-2012

# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 601PTZ Composite - For PTZ Cameras: CCTV + Control + Power

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

#### Outer Jacket Diameter:

Nom. Dia. (in.)
0.116

#### Outer Jacket Color Code Chart:

Number	Color
1	Blue

### Applicable Specifications and Agency Compliance

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

### Flame Test

UL Flame Test: NFPA 262

### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

#### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
67.000

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
35.000

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
15.000

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
12.000

#### Max. Operating Voltage - Other:

Voltage
300 V RMS

#### Max. Recommended Current:

Current
2.4 Amps per conductor @ 25°C

### Multi Conductor

#### Physical Characteristics

##### Conductor

###### AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
2	18	7x26	BC - Bare Copper	0.047

##### Insulation

###### Insulation Material:

Insulation Trade Name	Insulation Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

###### Insulation Color Code Chart:

Number	Color
1	Red

Distributed By:



# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 601PTZ Composite - For PTZ Cameras: CCTV + Control + Power

2	Black
---	-------

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

#### Outer Jacket Diameter:

Nom. Dia. (in.)
0.158

#### Outer Jacket Color Code Chart:

Number	Color
1	White

### Applicable Specifications and Agency Compliance

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

### Flame Test

UL Flame Test: NFPA 262

### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

#### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
30.000

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.500

#### Max. Operating Voltage - Other:

Voltage
300 V RMS

#### Max. Recommended Current:

Current
5 Amps per conductor @ 25°C

### Physical Characteristics (Overall)

#### Conductor

#### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material
Unjacketed

#### Overall Cable

Overall Nominal Diameter: 0.351 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -10°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 55.000 lbs/1000 ft.

Max. Recommended Pulling Tension: 130.000 lbs.

Min. Bend Radius (Install)/Minor Axis: 3.500 in.

# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 601PTZ Composite - For PTZ Cameras: CCTV + Control + Power

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	4/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	501PTZ

### Notes (Overall)

**Notes:** RG59 CCTV + 1 STP 22 AWG Control Grade + 2C 18 AWG CMP. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation. Banana Peel® US PATENT 7049523.

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
601PTZ 0001000	1,000 FT	65.000 LB	NONE		1 RG59 + 1 STP 22 + 2C18
601PTZ 000500	1,000 FT	67.000 LB	NONE		1 RG59 + 1 STP 22 + 2C18

Revision Number: 0    Revision Date: 04-14-2008

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.