

ENGLISH MEASUREMENT VERSION

603482 Multi-Conductor - Spec No. 39-2 (Aerial/Duct/Raceway)

For more Information please call

1-800-Belden1





Description

Physical Characteristics (Overall):

Conductor:

AWG

# Pairs	AWG	Stranding	Conductor Material
25.000	16	7X27	BC - Bare Copper

Total Number of Conductors

50

Insulation:

Insulation Material

Ins Material
HDPE - High Density Polyethylene

Outer Shield:

Outer Shield Material

Type	Outer Shield Material	% Coverage (%)
Tape	Corrugated Copper Tape	100

Outer Jacket:

Outer Jacket Material

Outer Jacket Material PE - Polyethylene

Overall Cabling:

Overall Nominal Diameter: 1.010 in.

Pair:

Pair Color Code Chart

Number	Color
1	White w/Blue Stripe
2	White w/Orange Stripe
3	White w/Green Stripe
4	White w/Brown Stripe
5	White w/Gray Stripe
6	Red w/Blue Stripe
7	Red w/Orange Stripe
8	Red w/Green Stripe
9	Red w/Brown Stripe
10	Red w/Gray Stripe
11	Black w/Blue Stripe
12	Black w/Orange Stripe
13	Black w/Green Stripe
14	Black w/Brown Stripe
15	Black w/Gray Stripe
16	Yellow w/Blue Stripe
17	Yellow w/Orange Stripe
18	Yellow w/Green Stripe
19	Yellow w/Brown Stripe
20	Yellow w/Gray Stripe
21	Purple w/Blue Stripe
22	Purple w/Orange Stripe
23	Purple w/Green Stripe



ENGLISH MEASUREMENT VERSION

603482 Multi-Conductor - Spec No. 39-2 (Aerial/Duct/Raceway)

24	Purple w/Brown Stripe
25	Purple w/Gray Stripe

Mechanical Characteristics (Overall):

Operating Temperature Range	-30°C To +80°C
Min. Bend Radius (Install):	8.200 in.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

Yes
01/01/2004
40-2
Υ
Υ
Y

Electrical Characteristics (Overall):

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft) 4.100

Max. Operating Voltage - Non-UL

Voltage 300 V RMS

Revision Number: 1 Revision Date: 05-14-2007

© 2007 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS). EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.