

7808WB Coax - RG-8X Type



For more Information
please call

1-800-Belden1

**Description:**

RG-8X type, 15 AWG solid .057" bare copper conductor, gas-injected foam HDPE insulation, Duobond® II + tinned copper braid shield (95% coverage), flooded water-resistant polyethylene jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	15	Solid	BC - Bare Copper	.057

Insulation**Insulation Material:**

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	.150

Outer Shield**Outer Shield Material:**

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Outer Shield Flooding Grease: PO - Polyolefin

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PE - Polyethylene

Overall Cable

Overall Nominal Diameter: 0.240 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

Bulk Cable Weight: 36 lbs/1000 ft.

Max. Recommended Pulling Tension: 74 lbs.

Min. Bend Radius (Install)/Minor Axis: 2.400 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

RG Type:	8/X
----------	-----

Suitability

Suitability - Outdoor:	Yes
------------------------	-----

Suitability - Aerial:	Yes - When supported by a messenger
-----------------------	-------------------------------------

Suitability - Burial:	Yes
-----------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)**Nom. Characteristic Impedance:**

Impedance (Ohm)

50

Nom. Inductance:

Inductance (μH/ft)

.060

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

23.0

Nominal Velocity of Propagation:

VP (%)

86

Nominal Delay:

Delay (ns/ft)

1.18

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

3.2

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

2.8

Maximum VSWR:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Max. VSWR
		5	6000	1.25:1

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
30	1.3
50	1.6
150	2.8
220	3.4
450	4.9
900	7.0
1500	9.1
1800	10.1
2000	10.7
2500	12.0
3000	13.4
3500	14.6
4500	16.7
5800	19.5
6000	19.8

Max. Power Rating:

Freq. (MHz) Rating (W)

30	1526
50	1186
150	673
220	556
450	382
900	286
1500	205
1800	187
2000	177
2500	156
3000	143
3500	100
4500	116
5800	102
6000	100

Max. Operating Voltage - Non-UL:

Voltage
300 V RMS

Sweep Test

Sweep Testing: 100% sweep tested to 6 GHz.

Misc. Information (Overall)**Notes (Overall)**

Notes: Belden® The Wire in Wireless®

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7808WB 0101000	1,000 FT	39.000 LB	BLACK	C	RF240 WIRELESS 50 OHM COAX WB
7808WB 010500	500 FT	18.000 LB	BLACK	C	RF240 WIRELESS 50 OHM COAX WB

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 09-30-2009

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.