

7887A Multi-Conductor - Super-Flexible, High-Performance Cable



For more Information
please call

1-800-Belden1



Description:

26 AWG stranded (19x38) bare copper conductor, polyethylene insulation, individually shielded with BC "French Braid", each quad w/26 AWG TC drain wire, color-coded PVC inner jacket w/overall PVC jacket and 20 AWG TC drain wire.

Physical Characteristics (Overall)

Conductor

AWG:

AWG Stranding	Conductor Material	Dia. (in.)
26 19x38	BC - Bare Copper	.020

Number of Quads: 12

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PE - Polyethylene	.045

Inner Shield

Inner Shield Material:

Coverage (%)
95

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.157

Inner Jacket Insulation Resistance: Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White, Black, Beige, Pink

Inner Jacket Color Code Chart:

Number	Color
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Purple
8	Gray
9	White
10	Black
11	Beige
12	Pink

Quad Inner Jacket

Quad Inner Jacket Color Code Chart:

Number	Color
1	Blue
2	White
3	Blue w/White Stripe

7887A Multi-Conductor - Super-Flexible, High-Performance Cable

4	White w/Blue Stripe
---	---------------------

Outer Shield

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	19x32	TC - Tinned Copper

Quad Shield

Quad Shield Material Type:	French Braid
Quad Shield Material:	BC - Bare Copper
Quad Shield %Coverage:	95 %
Quad Shield Drain Wire AWG:	26
Quad Shield Drain Wire Stranding:	7x38
Quad Shield Drain Wire Conductor Material:	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Purple
8	Gray
9	White
10	Black
11	Beige
12	Pink

Overall Nominal Diameter: 0.828 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +60°C
Bulk Cable Weight:	339 lbs/1000 ft.
Max. Recommended Pulling Tension:	535 lbs.
Min. Bend Radius (Install)/Minor Axis:	8.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

7887A Multi-Conductor - Super-Flexible, High-Performance Cable

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

40

Nom. Inductance:

Inductance (μH/ft)

.21

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

39.2

Nom. Cap. Between Cond. in a Quad Config.:

Capacitance (pF/ft)

57.4

Nominal Velocity of Propagation:

VP (%)

66

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

36

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.8

Max. Operating Voltage - UL:

Voltage

100 V RMS

Max. Recommended Current:

Current

1 Amp per conductor @ 25°C

Other Electrical Characteristic 1: 2/c 22 AWG equivalent DCR when connected to a 3-pin XLR.

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7887A B59500	500 FT	185.500 LB	BLACK, MATTE	C	12 QUAD PO FBRD PVC PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the

7887A Multi-Conductor - Super-Flexible, High-Performance Cable

compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.