

7977R Coax - Low Loss 50 Ohm Wireless RF Transmission Cable



For more Information
please call

1-800-Belden1

**Description:**

5.5 AWG solid .176" bare copper-covered aluminum conductor, foam HDPE insulation, Duobond® II (100% coverage) plus a tinned copper braid shield (85% coverage), PVC jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	5.5	Solid	BCCA - Bare Copper Covered Aluminum	.176

Insulation**Insulation Material:**

Insulation Material	Dia. (in.)
FHDPE - Foam High Density Polyethylene	.455

Outer Shield**Outer Shield Material:**

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	85

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 0.590 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +80°C
UL Temperature Rating:	80°C
Bulk Cable Weight:	163 lbs/1000 ft.
Max. Recommended Pulling Tension:	290 lbs.
Min. Bend Radius (Install)/Minor Axis:	5.900 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005
EU Directive 2002/96/EC (WEEE):	Yes

7977R Coax - Low Loss 50 Ohm Wireless RF Transmission Cable

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Series Type: RF 600

Flame Test

UL Flame Test: UL1666 Vertical Shaft

C(UL) Flame Test: FT4

Suitability

Suitability - Indoor: Yes

Suitability - Aerial: Yes - when supported by a messenger wire

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)**Nom. Characteristic Impedance:**

Impedance (Ohm)

50

Nom. Inductance:

Inductance (μH/ft)

0.060

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

24.6

Nominal Velocity of Propagation:

VP (%)

84

Nominal Delay:

Delay (ns/ft)

1.21

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

.53

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

1.8

Maximum VSWR:

Start Freq. (MHz)	Stop Freq. (MHz)	Max. VSWR
5.000	2690.000	1.25:1
2690.000	3290.000	2.00:1
3290.000	6000.000	1.43:1

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
30	.46
50	.61
150	.98
220	1.18
450	1.72
900	2.54
1500	3.40
1800	3.77
2000	4.01
2500	4.58

7977R Coax - Low Loss 50 Ohm Wireless RF Transmission Cable

3000	5.07
3500	5.56
4500	6.44
5800	7.56
6000	7.75

Max. Power Rating:

Freq. (MHz)	Rating (W)
30	5057
220	1975
450	1353
900	921
1500	691
1800	623
2000	587
3500	425
4500	368
5800	315
6000	309

Max. Operating Voltage - UL:

Voltage
300 V RMS

Notes (Overall)

Notes: 100% Sweep tested. Belden® The Wire in Wireless®.

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7977R 0101000	1,000 FT	174.000 LB	BLACK	C	#5 FPE SH FRPVC
7977R 010500	500 FT	89.500 LB	BLACK	C	#5 FPE SH FRPVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 10-02-2009

© 2012 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.