

83305 Multi-Conductor - MIL-W-16878/4 (Type E) Control and Instrumentation Cable



**Obsolete
Call
1-800-BELDEN1**

For more Information
please call

1-800-Belden1

Description:

22 AWG stranded (19x34) silver-plated copper conductors, cabled and color-coded, extruded TFE Teflon® insulation, silver-plated copper braid (90% coverage), TFE Teflon® tape-wrapped jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Conductors	AWG	Stranding	Conductor Material
1	22	19x34	SPC - Silver Plated Copper

Insulation**Insulation Material:**

Insulation Trade Name	Insulation Material	Wall Thickness (in.)
Teflon®	TFE - Tetrafluoroethylene	.010

Insulation Resistance: 100, 000 Megaohms/1000 ft. @ 500 V DC.

Outer Shield**Outer Shield Material:**

Type	Outer Shield Material	Coverage (%)
Braid	SPC - Silver Plated Copper	90

Outer Jacket**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (in.)
Teflon®	TFE - Tetrafluoroethylene	.010

Overall Cabling**Overall Cabling Color Code Chart:**

Color
White

Overall Nominal Diameter: 0.087 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -65°C To +200°C

Bulk Cable Weight: 8.900 lbs/1000 ft.

Max. Recommended Pulling Tension: 22.300 lbs.

Min. Bend Radius (Install)/Minor Axis: 0.750 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

Military Specification: MIL-W-16878/4 (Type E, except stranding, insulated conductors)

Flame Test

UL Flame Test: UL1685 UL Loading, VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

Non-Plenum Number: 83305E

Electrical Characteristics (Overall)**Nom. Inductance:**

Inductance (μH/ft)
.12

83305 Multi-Conductor - MIL-W-16878/4 (Type E) Control and Instrumentation Cable

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

57.9

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

14.3

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

11.3

Max. Operating Voltage - UL:

Voltage

600 V RMS

Max. Recommended Current:

Current

5 Amps per conductor at 25°C

Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 2 Revision Date: 05-14-2007

© 2008 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.