

## 8643 Multi-Conductor - Audio, Control and Instrumentation Cable



For more Information  
please call

1-800-Belden1



### Description:

30 AWG stranded (7x38) tinned copper conductors, conductors cabled around textile strength member, polypropylene insulation, paper separator, tinned copper braid shield (95% shield coverage), PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
3	30	7x38	TC - Tinned Copper	.012

#### Insulation

##### Insulation Material:

Insulation Material	Wall Thickness (in.)	Dia. (in.)
PP - Polypropylene	.006	.024

#### Outer Shield

##### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	TC - Tinned Copper	95

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.014

### Overall Cable

**Overall Cabling Fillers:** Textile Strength Member

#### Overall Cabling Lay Length & Direction:

Length (in.)	Direction	Twists (ft.)
.375	Left Hand Lay	32

#### Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red
3	White

**Overall Cabling Separator Material:** Paper Tape

**Overall Cabling Separator Thickness:** 0.001 in.

**Overall Nominal Diameter:** 0.096 in.

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -20°C To +105°C

**Non-UL Temperature Rating:** 105°C

**Bulk Cable Weight:** 7.600 lbs/1000 ft.

**Max. Recommended Pulling Tension:** 22.500 lbs.

**Min. Bend Radius (Install)/Minor Axis:** 1 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 10/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

#### Plenum/Non-Plenum

Plenum (Y/N): No

### Electrical Characteristics (Overall)

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

25

#### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

43

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

98.5

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

11.1

#### Max. Operating Voltage - UL:

Voltage

200 V RMS

#### Max. Recommended Current:

Current

0.9 Amps per conductor @ 25°C

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8643 060100	100 FT	1.100 LB	CHROME		3 #30 PP BRD PVC
8643 060250	250 FT	2.750 LB	CHROME		3 #30 PP BRD PVC

Revision Number: 1    Revision Date: 09-18-2008

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

## 8643 Multi-Conductor - Audio, Control and Instrumentation Cable

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.