

90SNS1PF Drop Connectors - Snap-N-Seal Right Angle "F" Male One-Piece Compression Connector



For more Information
please call

1-800-Belden1

**Description:**

Snap-N-Seal Right Angle F Male One-Piece Compression Connector, Compression Right Angle

Usage (Overall)

Suitable Applications: Broadband, CATV

Physical Characteristics (Connectivity)**Product Family:**

Part Number	Cable Type	Description	Post I.D. (in.)	Inner Pack	Sleeve I.D. (in.)	Sleeve Color	Outer Pack	Tool
90SNS1P6U	RG-6	Ultimate F Male Connector	0.191	40	0.315	Red	480	SNSUTL, CST596711, CST596

Connector Type: F Male One-Piece Compression

Nut Finish: NiTin Plated

Collar Finish: NiTin Plated

Body Components: Brass

Post Finish: Tin Plated

Terminal Finish: Silver Plated

O-Rings: Ethylene Propylene

Mechanical Characteristics (Connectivity)

Cable Insertion Force (Max./lbs.): < 20

Cable Retention Force: 40 lbs. min.

Temperature Rating: -40°C To +60°C, -40°F To +140°F

Salt Spray Exposure: Passes 1000 hours ASTM B 117

Moisture Migration: Passes ANSI/SCTE 60 2004

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 11/27/2008

Electrical Characteristics (Overall)

Return Loss (typical): -30 dB up to 20 MHz

Insertion Loss: -0.05 dB up to 20 MHz

RFI Shielding (typical): -120 dB up to 20 MHz

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

90SNS1PF Drop Connectors - Snap-N-Seal Right Angle "F" Male One-Piece Compression Connector

Revision Number: 0 Revision Date: 08-26-2011

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.