Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION

9911 Hook-up/Lead - UL AWM Style 1061

For more Information
please call

1-800-Belden1

Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	18	16x30	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.010

Overall Insulation

Overall Cable

Overall Nominal Diameter:	0.067 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL AWM Style:	1061
UL Rating:	300 V RMS, 80°C
CSA Rating:	300 V RMS, 80°C
CSA Type:	AWM I, A/B
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	VW-1
CSA Flame Test:	FT1

Plenum/Non-Plenum

Plenum (Y/N):	No

Related Documents:

No related documents are available for this product

Put Ups and Colors:

9911 Hook-up/Lead - UL AWM Style 1061

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9911 0011000	1,000 FT	7.000 LB	BROWN		#18 STR PVC BRN
9911 0021000	1,000 FT	7.000 LB	RED		#18 STR PVC RED
9911 0031000	1,000 FT	7.000 LB	ORANGE		#18 STR PVC ORG
9911 0041000	1,000 FT	7.000 LB	YELLOW		#18 STR PVC YEL
9911 0051000	1,000 FT	7.000 LB	GREEN, DARK		#18 STR PVC DGRN
9911 0071000	1,000 FT	7.000 LB	VIOLET		#18 STR PVC VIO
9911 0081000	1,000 FT	7.000 LB	GRAY		#18 STR PVC GRY
9911 0091000	1,000 FT	7.000 LB	WHITE		#18 STR PVC WHT
9911 0101000	1,000 FT	7.000 LB	BLACK		#18 STR PVC BLK
9911 0131000	1,000 FT	7.000 LB	BLUE, DARK		#18 STR PVC DBLU

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.