

9V28320 Flat - Vari-Twist® 9V283XX - .050 in. Pitch


 For more Information
 please call

1-800-Belden1

**Obsolete
Call**

1-800-BELDEN1

Description:

The shielded jacketed 9V283XX series provides shielding from external electrical interference and allows for greater flexibility, ease of termination, while providing exterior protection from the environment.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
10	28	7x36	TC - Tinned Copper

Conductor Spacing Center to Center Flat Section: .050 +/- .005

 Conductor Spacing Outside Center to Outside
 Center: .95 +/- .015

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.010

Substrate Thickness and Material: .010" Clear PVC

Insulation Resistance: >10, 000 Megaohms

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
2-28	7x36	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.038

Overall Cabling

Overall Nominal Thickness Flat Section: .127 +/- .012

Overall Nominal Thickness Twisted Section: .147

Overall Nominal Width: 1.10

Overall Flat Section Length: 2 +.5/-0

Overall Twisted Length: 18 in.

Flat Section Center to Center Spacing: 20 +/- .50

Pair

Pair Color Code Chart:

Number	Color
1	Brown/Tan
2	Red/Tan

9V28320 Flat - Vari-Twist® 9V283XX - .050 in. Pitch

3	Orange/Tan
4	Yellow/Tan
5	Green/Tan
6	Blue/Tan
7	Purple/Tan
8	Gray/Tan
9	White/Tan
10	Black/Tan

Spacing

Twisted Pair Spacing Center to Center: .100

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +105°C

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

UL AWM Style: 20081

UL Rating: 105°C, 300 V RMS, VW-1

Flame Test

UL Flame Test: VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

Surface Printing (Overall)

Surface Printing: BELDEN-T (UL LOGO) AWM STYLE 20081 VW-1 E12683

Electrical Characteristics (Overall)**Nom. Inductance:**

Description	Inductance (µH/ft)
@ 1 MHz	.13

Nom. Capacitance Conductor to Conductor:

Description	Capacitance (pF/ft)
@ 1 kHz (GSG) with shield grounded	35
@ 1 MHz (GSG) with shield grounded	29

Nominal Velocity of Propagation:

Description	VP (%)
	64

Nominal Delay:

Delay (ns/ft)
1.6 NS/FT. (GSG) with shield grounded

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
68.2 OHMS/1000 FT. MAX.

Nom. Attenuation:

Description	Freq. (MHz)	Attenuation (dB/100 ft.)
(GS) with shield grounded	10	5
(GS) with shield grounded	20	7.6
(GS) with shield grounded	30	9
(GS) with shield grounded	40	11.2
(GS) with shield grounded	50	12.4
(GS) with shield grounded	60	14.4
(GS) with shield grounded	70	16
(GS) with shield grounded	80	18
(GS) with shield grounded	90	20

9V28320 Flat - Vari-Twist® 9V283XX - .050 in. Pitch

(GS) with shield grounded	100	21.2
---------------------------	-----	------

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Current
1 Amp per conductor @ 20°C

Nominal Balanced Characteristic Impedance:

Description	Impedance (Ohm)
With shield grounded	100

Nominal Unbalanced Characteristic Impedance:

Description	Impedance (Ohm)
(GSG)with shield grounded	60

Dielectric Withstand Voltage: 2, 000 V RMS

Typical Balanced Crosstalk - dB Suppression:

Description	Start Freq. (MHz)	Stop Freq. (MHz)	Crosstalk (dB)
10 ft. sample length-near end	10	100	30
10 ft. sample length-far end	10	100	35

Typical Unbalanced Crosstalk:

Description	Pulse Rise Time (NS) (MHz)	Near End % (MHz)	Far End % (MHz)
10 ft. sample length with ground connected to shield	3	1.4	.9
10 ft. sample length with ground connected to shield	5	1	.4
10 ft. sample length with ground connected to shield	7	.8	.4

Notes (Overall)

Notes: The transition area is included in the twisted length to assure a full 2 inches of flat termination area. GS=Ground-Signal Mode.
 GSG=Ground-Signal-Ground Mode.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 1 Revision Date: 05-14-2007

© 2008 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.