

AX100703-X Connectivity Accessories - 110 CROSS-CONNECT, DISTRIBUTION RING, SMALL



For more Information
please call

1-800-Belden1

Description:

110 CROSS-CONNECT, DISTRIBUTION RING, SMALL

Usage (Overall)

Suitable Applications: IBDN System 1200, Telecom Room

Related Parts: 110 CROSS-CONNECT

Physical Characteristics (Connectivity)**Dimensions****Dimensions:**

Height (in.)	Width (in.)	Depth (in.)
4.500	5.700	1.500

Materials**Materials:**

Description	Material
Ring	Steel

Color

Color: Black

Weight

Weight: 0.792 lbs.

Packaging

Packaging: Individually packaged in a clear plastic bag.

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)**Suitability**

Suitability - Indoor: Yes - Indoor

Notes (Overall)

Notes: For additional information about this product, visit our website at <http://www.belden.com>

Product Family**Part Number List:**

Description	Item Number
WIRING BLOCK 100-PAIR W/O LEGS	AX100690-S
WIRING BLOCK 100-PAIR WITH LEGS	AX100691-S
WIRING BLOCK 300-PAIR W/O LEGS	AX100692-S
WIRING BLOCK 100-PAIR WITH LEGS WITH 4-PAIR CONNECTING BLOCKS	AX100693-S
WIRING BLOCK 100-PAIR WITH LEGS WITH 5-PAIR CONNECTING BLOCKS	AX100694-S
WIRING BLOCK 300-PAIR WITH LEGS WITH 4-PAIR CONNECTING BLOCKS	AX100695-S
WIRING BLOCK 300-PAIR WITH LEGS WITH 5-PAIR CONNECTING BLOCKS	AX100696-S
DISTRIBUTION RING, SMALL	AX100703-X
DISTRIBUTION RING, LARGE	AX100704-X
CABLE MANAGEMENT TROUGH W/O LEGS	AX100705-S
CABLE MANAGEMENT TROUGH WITH LEGS	AX100706-S
CONNECTING BLOCK 4-PAIR	AX100707-S
CONNECTING BLOCK 5-PAIR	AX100708-S

AX100703-X Connectivity Accessories - 110 CROSS-CONNECT, DISTRIBUTION RING, SMALL

LABEL STRIP CLEAR

AX100721-S

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 02-08-2011

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.