Detailed Specifications & Technical Data



23



AX100721-S Connectivity Accessories - 110 CROSS-CONNECT, LABEL STRIP

For more Information please call

1-800-Belden1

Description:

110 CROSS-CONNECT, LABEL STRIP, CLEAR

Usage (Overall)

Suitable Applications: IBDN System 1200, Telecom Room

Related Parts: 110 CROSS-CONNECT WIRING BLOCK

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (in.) Width (in.) Depth (in.)
0.583 | 7.874 | 0.244

Color

Color: Clear

Weight

Weight: 0.013 lbs.

Packaging

Packaging: Packaged 6 units in a clear plastic bag.

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes - Indoor

Notes (Overall)

Notes: For additionnal information about this product, visit our web site at http://www.belden.com

Product Family

Part Number List:

Description	Item Number
WIRING BLOCK 100-PAIR W/O LEGS	AX100690-S
WIRING BLOCK 100-PAIR WITH LEGS	AX100691-S
WIRING BLOCK 300-PAIR W/O LEGS	AX100692-S
WIRING BLOCK 100-PAIR WITH LEGS WITH 4-PAIR CONNECTING BLOCKS	AX100693-S
WIRING BLOCK 100-PAIR WITH LEGS WITH 5-PAIR CONNECTING BLOCKS	AX100694-S
WIRING BLOCK 300-PAIR WITH LEGS WITH 4-PAIR CONNECTING BLOCKS	AX100695-S
WIRING BLOCK 300-PAIR WITH LEGS WITH 5-PAIR CONNECTING BLOCKS	AX100696-S
DISTRIBUTION RING, SMALL	AX100703-X
DISTRIBUTION RING, LARGE	AX100704-X
CABLE MANAGEMENT TROUGH W/O LEGS	AX100705-S
CABLE MANAGEMENT TROUGH WITH LEGS	AX100706-S
CONNECTING BLOCK 4-PAIR	AX100707-S
CONNECTING BLOCK 5-PAIR	AX100708-S
LABEL STRIP CLEAR	AX100721-S

Related Documents:

No related documents are available for this product

Detailed Specifications & Technical Data





AX100721-S Connectivity Accessories - 110 CROSS-CONNECT, LABEL STRIP

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100721-S	1 EA	0.013 LB			LABEL STRIP, CLEAR

Revision Number: 0 Revision Date: 02-08-2011

© 2012 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.