


## AX102032 Panels - FiberExpress 1U Manager



For more Information  
please call

1-800-Belden1

**Description:**

FiberExpress Cable Management Accessory, 1U, Black.

**Usage (Overall)**

**Suitable Applications:** FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room

**Related Parts:** FiberExpress Manager 1U Rack Mount Patch Panel

**Physical Characteristics (Connectivity)****Capacity**

**Max. Capacity:** Bracket opening of 1.6 in. X 2.7 in. (1U)

**Dimensions****Dimensions:**

Height (in.)	Width (in.)	Depth (in.)
1.720	17.200	5.810

**Materials****Materials:**

Description	Material
Panel	Steel

**Color**

**Color:** Black

**Included Parts**

**Included Parts:** 2 Screws (10-32); 1 Instruction Sheet; 1 Administration Label; 1 PFFA Label; 2 Velcro Straps.

**Packaging**

**Packaging:** Individually packaged in a cardboard box.

**Mechanical Characteristics (Connectivity)**

**Storage Temperature Range:** -40°C To +70°C

**Operating Temperature Range:** -10°C To +60°C

**Applicable Specifications and Agency Compliance (Overall)****Suitability**

**Suitability - Indoor:** Yes

**Transmission Characteristics (Connectivity)****Notes (Overall)**

**Notes:** For proper installation refer to Installation Guide PX103404 included with the product or visit our web site at <http://www.belden.com>

**Product Family****Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX102032	1 EA	2.076 LB			FXM 1U RACK MOUNT PANEL

## AX102032 Panels - FiberExpress 1U Manager

Revision Number: 0    Revision Date: 03-30-2010

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.