Detailed Specifications & Technical Data





AX102782 Panels - Identification Tube

For more Information please call

1-800-Belden1

Description:

Identification Tube 5.5 in with label

Usage (Overall)

Suitable Applications: Telecommunications Room, Main Distribution Room, Data Centers

Related Parts: Keyconnect Patch Panels 1U24 Ports, 2U48 Ports

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Width (in.) Length (in.) 0.580 5.500

Materials

Materials:

Description	Material	Color
Identification Tube	Plastic - UL94V-0	Clear

Packaging

Packaging: 100 per bag

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For additional information about this product refer visit our web site at http://www.belden.com.

Product Family

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX102782	1 EA	0.000 LB			LABEL HOLDER 5.5 IN (100/PK)

Revision Number: 0 Revision Date: 09-22-2010

© 2012 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

