

## AX104285 Connectivity Accessories - FiberExpress Brilliance Field cleaver



For more Information  
please call

1-800-Belden1

**Description:**

FiberExpress Brilliance Field Cleaver

**Usage (Overall)****Suitable Applications:**

Indoor termination of fiber cables: Patch panels, Communication outlets, Fiber-to-the-desk, Distribution frames, Direct termination to equipment, Fiber cable repair, Campus, Customer premise / Access network.

**Related Parts:**

Brilliance connectors, Breakout kits, FiberExpress Brilliance Field Kit, Optimax

**Physical Characteristics (Connectivity)****Dimensions****Dimensions:**

Height (in.)	Width (in.)	Length (in.)
1.750	75.000	4.500

**Color****Color:**

Black

**Weight****Weight:**

0.282 lbs.

**Packaging****Packaging:**

Individually packaged in a cardboard box.

**Mechanical Characteristics (Connectivity)****Storage Temperature Range:**

-20°C To +60°C

**Tool Compatibility:**

FIELD CLEAVER REPLACEMENT LEAF SPRING AX104294, FIBER FIELD CLEAVER REPLACEMENT BLADE AX103149

**Mechanical Specifications:**

Feature	Specification
Blade life	Typical 1000 cleaves
Blade type	Ceramic
Cleave length	From 2 to 20 mm (graduated scale)
Coating diameter	250 and 900 µm

**Applicable Specifications and Agency Compliance (Overall)****Suitability****Suitability - Indoor:**

Yes - Indoor

**Notes (Overall)**

**Notes:** For additional information about this product refer to product bulletin NP308, or visit our web site at <http://www.belden.com>.

**Product Family****Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX104285	1 EA	0.480 LB			Brilliance Field Cleaver

## AX104285 Connectivity Accessories - FiberExpress Brilliance Field cleaver

Revision Number: 0    Revision Date: 08-27-2010

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.