Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION

AX203432 Cable Assemblies - FiberExpress MPO Assembly





For more Information please call

1-800-Belden1

Description:

FiberExpress MPO Cable Assembly, Single-Mode (OS2), 24-Fiber, MPO(F)/APC - MPO(F)/APC, X-Over (type C), Fan-Out Length: 1m, Fan-Out Construction: 3.0mm, Fan-Out Geometry: None, 1 Pulling Eye, 46m (150.9ft)

Usage (Overall)

Suitable Applications:	Data Centers, Main Equipment Rooms,Telecommunications Rooms
Related Parts:	FiberExpress Manager Modules and FiberExpress Ultra Cassettes

Multi Conductor

Physical Characteristics

Overall Cabling

Overall Cabling Fillers:	Refer to cable Technical Specifications

Overall Diameter

Individual Cable Diameter:	0.311 in.

Physical Characteristics (Connectivity)

Fiber Type

Fiber Type:	SM, (OS2)

Wiring Scheme

Wiring Scheme:	TIA/EIA 568-C.3

Packaging

Packaging:	Individually packaged

Mechanical Characteristics (Connectivity)

Storage Temperature Range:	-40°C To +75°C
Operating Temperature Range:	-10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating:	Plenum
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	TIA 568.C.3
Safety Listing:	ACA, Bi-national (UL/CSA) Standard Listed

Suitability

Suitability - Indoor:	Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

AX203432 Cable Assemblies - FiberExpress MPO Assembly

Notes: Ref PEC CODE: NXC-UPSX-PHXFGN-PHAFGN-O-0046

Product Family

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc

Revision Number: 0 Revision Date: 09-11-2009

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.