

C5503 Multi-Conductor - 600V Teck90 Cable



For more Information
please call

1-800-Belden1

**Description:**

14 AWG stranded (7x22) bare copper conductors, 14 AWG bare copper ground wire, aluminum interlocked armor, .030" (.76mm) XLPE insulation, PVC inner jacket, PVC outer jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Conductors	AWG	Stranding	Conductor Material
5	14	7x22	BC - Bare Copper

Ground Wire

Ground Wire (Y/N):	Y
Ground Wire AWG:	14
Ground Wire Stranding:	7x22
Ground Wire Conductor Material:	BC - Bare Copper

Insulation**Insulation Material:**

Insulation Material
XLPE - Cross Linked Polyethylene

Outer Shield**Outer Shield Material:**

Outer Shield Material
Unshielded

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
.47

Outer Jacket over Armor (y/n):	Y
--------------------------------	---

Outer Jacket over Armor

Outer Jacket Material over Armor (y/n):	PVC - Polyvinyl Chloride
---	--------------------------

Armor

Armor Type:	Interlocked
Armor Material:	Aluminum
Diameter over Armor:	.66

Overall Cable**Overall Cabling Color Code Chart:**

Number	Color
1-5	Black and Numbered

Overall Nominal Diameter:	0.740 in.
---------------------------	-----------

Mechanical Characteristics (Overall)

Wet Temperature Range:	-40°C To +90°C
Dry Temperature Range:	-40°C To +90°C
Non-UL Temperature Rating:	90°C Wet/Dry
Bulk Cable Weight:	284 lbs/1000 ft.
Max. Recommended Pulling Tension:	164 lbs.
Min. Bend Radius (Install)/Minor Axis:	9 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

CSA Specification:	C22.2 #131; Hazardous Location; C22.2 #0.3 Clause 4.31 Low Acid Gas
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

CSA Flame Test:	FT4
-----------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

2.6

Max. Operating Voltage - Non-UL:

Voltage

600 V RMS

Max. Recommended Current:

Current

12 Amps per conductor @ 25°C

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

C5503 Multi-Conductor - 600V Teck90 Cable

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.