



C6F1100000 Cable Assemblies - Cat 6 Shielded Modular Cord



For more Information
please call

1-800-Belden1

**Description:**

Cat 6 Shielded Patchcord, 4 Pair, 24 AWG Solid, CMR, T568A/B-T568A/B,

Usage (Overall)

Suitable Applications: IBDN Shielded System 2400, TIA Category 6, ISO Class E, 1000BASE-T

Related Parts: Cat6+ Shielded KeyConnect Modular Jacks, Shielded Patch Panels

Multi Conductor**Physical Characteristics****Conductor****AWG:**

# Conductors	# Pairs	AWG	Stranding	Conductor Material
8	4	24	Solid	BC - Bare Copper

Insulation**Insulation Material:**

Insulation Material
PO - Polyolefin

Outer Shield**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material
Shield	Foil	AL - Aluminum

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Cabling Fillers: Cross Web

Overall Diameter

Overall Nominal Diameter: 0.260 in.

Individual Cable Diameter: 0.260 in.

Cable Characteristics (Connectivity)**Outer Shield**

Outer Shield Drain Wire Diameter: 26 AWG

Physical Characteristics (Connectivity)**Materials****Materials:**

Description	Type	Material
Plug	RJ45	Polycarbonate
Boot		Elastomer
Front Connection	Blades	Phosphor Bronze with 50u inch Gold over Nickel Plating

Color

C6F1100000 Cable Assemblies - Cat 6 Shielded Modular Cord

Boot Color: Same as Cable

Wiring Scheme

Wiring Scheme: T568A/B-T568A/B

Packaging

Packaging: Individually packaged in a clear plastic bag.

Mechanical Characteristics (Connectivity)

Plug / Jack Compatibility: RJ45

Termination Interface:

Termination	Connection	Durabilities
RJ45	Mated Connection	750 Cycles

Max. Recommended Pull Tension: 11.250 lbs.

Min. Bend Radius (Overall Cable): 2.080 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

UL Rating: Riser

Other Standards: FCC Part 68, Subpart F, IEC 60603-7

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2011

MII Order #39 (China RoHS): EUP 50

Telecommunications Standards: Category 6 - TIA 568.C.2, Class E - ISO/IEC 11801:2002

Safety Listing: Bi-national (UL/CSA) Standard Listed

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Dielectric Strength: 1,000 V RMS @ 60 Hz for 1 minute

Current Rating: 1.500 A

Insulation Resistance: 500 M-Ohm Minimum

Max. Contact Resistance: 20 m-Ohm

Notes (Overall)

Notes: Last 3-digits 'xxx' specify length in feet; Available from 1 ft (001) to 15 ft (015) by increment of 1 ft, 20 ft (025) and 25 ft (025).

Product Family**Product List:**

Length	Blue	Gray	White	Black
1 ft. (0.3 m)	C6F1106001	C6F1108001	C6F1109001	C6F1100001
2 ft. (0.6 m)	C6F1106002	C6F1108002	C6F1109002	C6F1100002
3 ft. (0.9 m)	C6F1106003	C6F1108003	C6F1109003	C6F1100003
4 ft. (1.2 m)	C6F1106004	C6F1108004	C6F1109004	C6F1100004
5 ft. (1.5 m)	C6F1106005	C6F1108005	C6F1109005	C6F1100005
6 ft. (1.8 m)	C6F1106006	C6F1108006	C6F1109006	C6F1100006
7 ft. (2.1 m)	C6F1106007	C6F1108007	C6F1109007	C6F1100007
8 ft. (2.4 m)	C6F1106008	C6F1108008	C6F1109008	C6F1100008
9 ft. (2.7 m)	C6F1106009	C6F1108009	C6F1109009	C6F1100009
10 ft. (3.0 m)	C6F1106010	C6F1108010	C6F1109010	C6F1100010
11 ft. (3.4 m)	C6F1106011	C6F1108011	C6F1109011	C6F1100011
12 ft. (3.7 m)	C6F1106012	C6F1108012	C6F1109012	C6F1100012
13 ft. (4.0 m)	C6F1106013	C6F1108013	C6F1109013	C6F1100013
14 ft. (4.3 m)	C6F1106014	C6F1108014	C6F1109014	C6F1100014

C6F1100000 Cable Assemblies - Cat 6 Shielded Modular Cord

15 ft. (4.6 m)	C6F1106015	C6F1108015	C6F1109015	C6F1100015
20 ft. (6.1 m)	C6F1106020	C6F1108020	C6F1109020	C6F1100020
25 ft. (7.6 m)	C6F1106025	C6F1108025	C6F1109025	C6F1100025

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 06-22-2011

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.