


C6F1300000 Cable Assemblies - CAT 6 Shielded Pigtails, CMR, T568B-open

For more Information
please call

1-800-Belden1

**Description:**

CAT 6 Shielded Pigtail, 4 Pair, 24 AWG Solid, CMR, T568B-Open,

Usage (Overall)

Suitable Applications: IBDN Shielded System 2400, TIA Category 6, ISO Class E, 1000BASE-T

Related Parts: Cat 6+ Shielded KeyConnect Modular Jacks, Shielded Patch Panels,

Multi Conductor**Physical Characteristics****Conductor****AWG:**

# Conductors	# Pairs	AWG	Stranding	Conductor Material
8	4	24	Solid	BC - Bare Copper

Insulation**Insulation Material:**

Insulation Material
PO - Polyolefin

Outer Shield**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material
Shield	Foil	AL - Aluminum

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Cabling Fillers: Cross Web

Overall Diameter

Overall Nominal Diameter: 0.260 in.

Individual Cable Diameter: 0.260 in.

Cable Characteristics (Connectivity)**Outer Shield**

Outer Shield Drain Wire Diameter: 26 AWG

Physical Characteristics (Connectivity)**Materials****Materials:**

Description	Type	Material
Plug	RJ45	Polycarbonate
Boot		Elastomer
Front Connection	Blades	Phosphor Bronze with 50u inch Gold over Nickel Plating

Color

C6F1300000 Cable Assemblies - CAT 6 Shielded Pigtails, CMR, T568B-open

Boot Color: Same as cable

Wiring Scheme

Wiring Scheme: T568B-Open

Packaging

Packaging: Individually packaged in a clear plastic bag.

Mechanical Characteristics (Connectivity)

Plug / Jack Compatibility: RJ45

Termination Interface:

Termination	Connection	Durabilities
RJ45	Mated Connection	750 Cycles

Max. Recommended Pull Tension: 11.250 lbs.

Min. Bend Radius (Overall Cable): 2.080 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

UL Rating: Riser

Other Standards: FCC Part 68, Subpart F, IEC 60603-7

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2011

MII Order #39 (China RoHS): EUP 50

Telecommunications Standards: Category 6 - TIA 568.C.2, Class E - ISO/IEC 11801:2002

Safety Listing: Bi-national (UL/CSA) Standard Listed

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Dielectric Strength: 1,000 V RMS @ 60 Hz for 1 minute

Current Rating: 1.500 A

Insulation Resistance: 500 M-Ohm Minimum

Max. Contact Resistance: 20 m-Ohm

Notes (Overall)

Notes: Last 3-digits 'xxx' specify length in feet; Available from 15ft (015) to 100ft (100) by increment of 5 ft.

Product Family**Product List:**

Length	Blue	Gray	White	Black
15 ft. (4.6 m)	C6F1306015	C6F1308015	-	-
20 ft. (6.1 m)	C6F1306020	C6F1308020	-	-
25 ft. (7.6 m)	C6F1306025	C6F1308025	-	-
30 ft. (9.1 m)	C6F1306030	C6F1308030	-	-
35 ft. (10.7 m)	C6F1306035	C6F1308035	-	-
40 ft. (12.2 m)	C6F1306040	C6F1308040	-	-
45 ft. (13.7 m)	C6F1306045	C6F1308045	-	-
50 ft. (15.2 m)	C6F1306050	C6F1308050	-	-
55 ft. (16.8 m)	C6F1306055	C6F1308055	-	-
60 ft. (18.3 m)	C6F1306060	C6F1308060	-	-
65 ft. (18.3 m)	C6F1306065	C6F1308065	-	-
70 ft. (21.3 m)	C6F1306070	C6F1308070	-	-
75 ft. (22.9 m)	C6F1306075	C6F1308075	-	-
80 ft. (24.4 m)	C6F1306080	C6F1308080	-	-

C6F1300000 Cable Assemblies - CAT 6 Shielded Pigtails, CMR, T568B-open

85 ft. (25.9 m)	C6F1306085	C6F1308085
90 ft. (27.4 m)	C6F1306090	C6F1308090
95 ft. (29.0 m)	C6F1306095	C6F1308095
100 ft. (30.5 m)	C6F1306100	C6F1308100

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 06-22-2011

© 2012 Belden, Inc.
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.