

Part Number: C0681A

Revision Level: 1

Date: 3/26/2009

4C 24 AWG 7/32 TC FMPP OAS PVC

LO-CAP COMPUTER CABLE

A. CONSTRUCTION

Conductor: #24 AWG 7/32 Tinned Copper
 Insulation: 0.016" Wall Foamed Polypropylene
 Cable: 4 Conductors cabled LHL with aluminum/polyester
 (foil out) & #24 AWG 7/32 TC drain wire
 Braid: Tinned Copper Braid
 70% Nom. Coverage
 Jacket: 0.032" Wall Polyvinyl Chloride
 Print Legend: *CAROL (R) 24 AWG -- C0681A -- 75C E111240-8 CM (UL) C (UL) CMH OR 80C 30V AWM*

DIAMETERS

0.024" nom.
 0.056" nom.
 0.141" nom.
 0.163" nom.
 0.227" +/- 0.011"
STYLE 2919 LOW VOLTAGE COMPUTER CABLE -- MADE IN USA (DATE CODE) (PRINTED)

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM (UL) c (UL) CMH
UL Subject 758	AWM Style 2919

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C (CM); 80C (AWM)
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms (CM) / 30 Vrms (AWM)
CONDUCTOR D.C. RESISTANCE:	25.7 Ohms/1000 ft. nom. @ 20C
SHIELD RESISTANCE:	3.8 Ohms/1000 ft. nom. @ 20C
MUTUAL CAPACITANCE:	11.9 pF/ft. @ 1 kHz nom.
GROUND CAPACITANCE:	21.5 pF/ft. @ 1 kHz nom.
CHARACTERISTIC IMPEDANCE:	107 Ohms @ 1 MHz nom.

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Lt. Green