

Part Number: C0940A

Revision Level: 1

Date: 7/11/2007

**4C 28 7/36 TC SR-PVC OAS BRAID PVC**

**COMPUTER CABLE**

**A. CONSTRUCTION**

**DIAMETERS**

Conductor:	#28 AWG 7/36 Tinned Copper	0.015" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.035" nom.
Cable:	4 Conductors @ 1.50" LHL - Aluminum/polyester (Foil Out) - #28 7/36 TC D.W.	0.090" nom.
Braid	Tinned Copper Braid 65% nom. Coverage	0.112" nom.
Jacket:	0.032" Polyvinyl Chloride	0.176" +/- 0.009"
Print Legend:	<b>CAROL (R) 28 AWG -- C0940A -- 75C E60233-8 (UL) CL2 OR AWM STYLE 2464 --- CSA LL69381 CMG -- MADE IN USA</b>	

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 13	Type CL2
UL Standard 758	AWM Style 2464
CSA International	Type CMG

**C. ELECTRICAL PROPERTIES**

TEMPERATURE:	75C (CL2) / 80C (2464) / 60C (CMG)
SUGGESTED WORKING VOLTAGE (V <sub>rms</sub> ):	300 V <sub>rms</sub>
CONDUCTOR D.C. RESISTANCE:	67.5 Ohms/1000 ft nom
SHIELD RESISTANCE:	5 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	26.01 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	46.82 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	72.5 Ohms @ 1MHz nom

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Light Green