

Part Number: C1202

Revision Level: 1

Date: 11/6/2007

**2C 18 AWG 41/34 TC RUBBER OAS CAROLPRENE\***

**Audio/Video & Broadcast Cable**

**A. CONSTRUCTION**

Conductor: #18 AWG 41/34 Tinned Copper  
 Insulation: 0.020" Wall Rubber  
 Cable: 2C @ 1.75" LHL with jute filler & overall mylar wrap.  
 Braid: #36 AWG Tinned Copper, 80% Min. Coverage  
 Jacket: 0.035" Wall Carolprene\* - Black  
 Print Legend: **CAROL -- C1202A -- VW-1 MADE IN USA**

**DIAMETERS**

0.049" nom.  
 0.091" nom.  
 0.182" nom.  
 0.182" nom.  
 0.295" +/- 0.015"

**B. INDUSTRY APPROVALS**

None

**C. ELECTRICAL PROPERTIES**

TEMPERATURE: 60C  
 SUGGESTED WORKING VOLTAGE (V<sub>rms</sub>): 300V  
 CONDUCTOR D.C. RESISTANCE: 7.1 Ohms/1000 ft nom  
 SHIELD RESISTANCE: 3.2 Ohms/1000 ft nom

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	White
2	Black