

Part Number: C1204

Revision Level: 4

Date: 11/20/2007

4C 18 AWG 41/34 TC RUBBER OAS CAROLPRENE

CONTROL CABLE

A. CONSTRUCTION

Conductor: #18 AWG 41/34 Tinned Copper
 Insulation: 0.020" Wall Rubber
 Cable: 4 conductors @ 2.50" LHL with jute filler
 & overall mylar wrap.
 Braid #36 AWG Tinned Copper
 80% Min. coverage
 Tape: Cotton Separator
 Jacket: 0.035" Wall Carolprene* - Black
 Print Legend: *CAROL C-1204A VW-1 MADE IN USA*

DIAMETERS

0.049" nom.
 0.091" nom.
 0.220" nom.
 .240" nom.
 0.260" nom.
 0.330" +/- 0.017"

B. INDUSTRY APPROVALS

NONE

C. ELECTRICAL PROPERTIES

TEMPERATURE: 60 C
 SUGGESTED WORKING VOLTAGE (Vrms): 300Vrms
 CONDUCTOR D.C. RESISTANCE: 7.1 Ohms/1000 ft nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green