

Part Number: C1212

Revision Level: 3

Date: 11/20/2007

12C 18 AWG 41/34 TC RUBBER OAS CAROLPRENE*

CONTROL CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#18 AWG 41/34 Tinned Copper	0.049" nom.
Insulation:	0.020" Wall Rubber	0.091" nom.
Cable:	12 conductors @ 4.00" LHL with jute filler & overall mylar wrap.	0.378" nom.
Braid	#36 AWG Tinned Copper 80% Min. Coverage	0.400" nom.
Tape:	Cotton Separator	0.410" nom.
Jacket:	0.065" Wall Carolprene* - Black	0.555" +/- 0.028"
Print Legend:	CAROL C-1212A VW-1 MADE IN USA	

B. INDUSTRY APPROVALS

NONE

C. ELECTRICAL PROPERTIES

TEMPERATURE:	60 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	7.1 Ohms/1000 ft nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black	11	White/Black
2	White	12	White/Red
3	Red		
4	Green		
5	Blue		
6	Brown		
7	Yellow		
8	Orange		
9	Gray		
10	Purple		