

Part Number: C1313

Revision Level: 3

Date: 11/14/2007

8C 20 AWG 26/34 TC RUBBER OAS RUBBER

CONTROL CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#20 AWG 26/34 Tinned Copper	0.038" nom.
Insulation:	0.020" Wall Rubber	0.080" nom.
Cable:	8 conductors @ 3.00" LHL with jute fillers & mylar wrap.	0.290" nom.
Braid	#36 AWG Tinned Copper 80% min. coverage	0.310" nom.
Tape:	Cotton Separator	0.320" nom.
Jacket:	0.035" Wall Rubber - Black	0.385" +/- 0.019"
Print Legend:	CAROL (R) C-1313A MADE IN USA	

B. INDUSTRY APPROVALS

NONE

C. ELECTRICAL PROPERTIES

TEMPERATURE:	60 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	11.3 Ohms/1000 ft nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green
5	Blue
6	Brown
7	Yellow
8	Orange