

Part Number: C1602

Revision Level: 3

Date: 11/20/2007

**2C 16 AWG 65/34 TC RUBBER OAS CAROLPRENE\***

**CONTROL CABLE**

**A. CONSTRUCTION**

**DIAMETERS**

Conductor:	#16 AWG 65/34 Tinned Copper	0.060" nom.
Insulation:	0.025" Wall Rubber	0.110" nom.
Cable:	2 conductors @ 2.00" LHL with jute filler & overall mylar wrap.	0.235" nom.
Braid	#36 AWG Tinned Copper 80% Min. Coverage	0.255" nom.
Tape:	Cotton Separator	0.265" nom.
Jacket:	0.035" Wall Carolprene* - Black	0.335" +/- 0.017"
Print Legend:	<b>CAROL C-1602A VW-1 MADE IN USA</b>	

**B. INDUSTRY APPROVALS**

NONE

**C. ELECTRICAL PROPERTIES**

TEMPERATURE:	60 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	4.5 Ohms/1000 ft nom

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White