

Part Number: C1608

Revision Level: 3

Date: 11/21/2007

8C 16 AWG 65/34 TC RUBBER OAS CAROLPRENE*

CONTROL CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#16 AWG 65/34 Tinned Copper	0.060" nom.
Insulation:	0.025" Wall Rubber	0.110" nom.
Cable:	8 conductors @ 4.00" LHL with jute filler & overall mylar wrap.	0.400" nom.
Braid	#36 AWG Tinned Copper 80% Min. coverage	0.420" nom.
Tape:	Cotton Separator	0.430" nom.
Jacket:	0.040" Wall Carolprene* - Black	0.510" +/- 0.026"
Print Legend:	CAROL C-1608A VW-1 MADE IN USA	

B. INDUSTRY APPROVALS

NONE

C. ELECTRICAL PROPERTIES

TEMPERATURE:	60 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	4.5 Ohms/1000 ft nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	White
3	Red
4	Green
5	Blue
6	Brown
7	Yellow
8	Orange