

Part Number: C2409A

Revision

Date:

7/12/2012

**2C/14 19/.0147TC UNSH PVC / PVC**

**COMMUNICATION & CONTROL CABLE**

**A. CONSTRUCTION**

Conductor: 14 AWG 19/.0147 TC  
 Insulation: .030" Wall, Polyvinyl Chloride  
 Cable Core: 2C @ 6.00" LHL  
 Jacket: .032" Wall, Polyvinyl Chloride (PVC)  
 Print Legend: **CAROL (R) 14 AWG -- C2409A -- 75C E60233-8 (UL)  
 CL3 OR AWM STYLE 2587 --- CSA LL69381 CMH --  
 MADE IN USA (Date code) (Seq Footage)**

**DIAMETERS**

.071" nom  
 .131" nom  
 .262" nom  
 .326" nom

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 13	Type CL3
UL Standard 758	AWM Style 2587
CSA International	Type CMH

**C. ELECTRICAL PROPERTIES**

Temperature: 75C  
 Suggested Working Voltage: 300V  
 Conductor DCR: 2.7 Ohms/1000 ft nom  
 Mutual Capacitance: 29 pF/ft @ 1kHz nom

**D. COLOR CODE**

Cond	COLOR
1	BLACK
2	WHITE