

Part Number: C2410A Revision Date: 1/31/2013

2C/12 19/.0185TC UNSH PVC / PVC

COMMUNICATION & CONTROL CABLE

A. CONSTRUCTION

Conductor: 12 AWG 19/.0185 TC
 Insulation: .032" Wall, Polyvinyl Chloride
 Cable Core: 2C @ 6.00" LHL
 Jacket: .032" Wall, Polyvinyl Chloride (PVC)
 Print Legend: **CAROL (R) 12 AWG -- C2410A-- 75C E60233-8 (UL) CL3
 OR AWM STYLE 2587 --- CSA LL69381 60C CMG -- MADE
 IN USA**

DIAMETERS

.092" nom
 .156" nom
 .366" nom

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3
UL Standard 758	AWM Style 2587
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature: -20°C to +90°C
 Suggested Working Voltage: 600V (Max)
 Conductor DCR: 1.68 Ohms/M' @ 20°C
 Mutual Capacitance: 31.5 pF/ft @ 1kHz nom

D. COLOR CODE

Cond	COLOR
1	BLACK
2	WHITE

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____