

Part Number: C2430A

Revision

Date:

1/31/2013

4C/14 19/.0147TC UNSH PVC / PVC**COMMUNICATION & CONTROL CABLE****A. CONSTRUCTION**

Conductor:	14 AWG 19/.0147 TC	.071" nom
Insulation:	.032" Wall, Polyvinyl Chloride	.135" nom
Cable Core:	4C @ 6.00" LHL	
Jacket:	.032" Wall, Polyvinyl Chloride (PVC)	.391" nom
Print Legend:	CAROL (R) 14 AWG -- C2430A-- 75C E60233-8 (UL) CL3 OR AWM STYLE 2587 -- MADE IN USA	

DIAMETERS**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 13	Type CL3
UL Standard 758	AWM Style 2587

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +90°C
Suggested Working Voltage:	600V
Conductor DCR:	2.65 Ohms/M' @ 20°C (Max)
Mutual Capacitance:	28.2 pF/ft @ 1kHz nom

D. COLOR CODE

Cond	COLOR
1	BLACK
2	WHITE
3	RED
4	GREEN

E. CUSTOMER APPROVAL

Signature: _____
Date: _____