

General Cable Product Data Sheet

Part Number: C3352

Revision Level: 0

Date: 7/7/2007

2P 22 7/30 TC FLEX OAS PVDF

TYPE CL2P

A. CONSTRUCTION

DIAMETERS

Conductor:	#22 AWG 7/30 Tinned Copper	0.030" nom.
Insulation:	0.007" Wall FLEXGUARD*	0.044" nom.
Pairing	4 conductors into 2 pairs @ 1.50" LHL.	
Cable:	2 pairs @ 2.50" LHL, aluminum/polypro (foil in) & # 24 7/32 TC drain wire.	0.137" nom.
Jacket:	0.010" Wall PVDF – Natural -Plenum ripcord under jacket.	0.157" +/- 0.008"
Print Legend:	CAROL (R) 22 AWG -- C3352 -- 60C E60233-8 CL2P -- MADE IN USA DATE CODE (PRINT EVERY 2 FT)	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL2P

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V _{rms}):	150 V _{rms} (CL2P)
CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft. nom. @ 20C

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black & Yellow
2	Red & Purple

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.