

# General Cable Product Data Sheet

Part Number: C3362

Revision Level: 0

Date: 7/7/2007

**2P 18 7/26 BC FLEX OAS PVDF**

**TYPE CL2P / CMP**

## **A. CONSTRUCTION**

## **DIAMETERS**

Conductor:	#18 AWG 7/36 Bare Copper	0.047" nom.
Insulation:	0.008" Wall FLEXGUARD*	0.063" nom.
Pairing	4 conductors into 2 pairs @ 1.50" LHL.	
Cable:	2 pairs @ 2.50" LHL, aluminum/polypro (foil in) & # 22 7/30 TC drain wire.	0.185" nom.
Jacket:	0.010" Wall PVDF – Natural -Plenum ripcord under jacket.	0.205" +/- 0.010"
Print Legend:	<b><i>CAROL (R) 18 AWG -- C3362 -- 60C E60233-8 CL2P OR CMP(UL)C(UL) -- MADE IN USA DATE CODE (PRINT EVERY 2 FT)</i></b>	

## **B. INDUSTRY APPROVALS**

National Electrical Code UL Standard 13	Article 725 Type CL2P
National Electrical Code UL Standard 444	Article 800 Type CMP

## **C. ELECTRICAL PROPERTIES**

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	150 Vrms (CL2P); 300 Vrms (CMP)
CONDUCTOR D.C. RESISTANCE:	5.6 Ohms/1000 ft. nom. @ 20C

## **D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black & Yellow
2	Red & Purple

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

\*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.