

General Cable Product Data Sheet

Part Number: C3364

Revision Level: 0

Date: 7/7/2007

4P 18 7/26 BC FLEX OAS PVDF

TYPE CL2P / CMP

A. CONSTRUCTION

DIAMETERS

Conductor:	#18 AWG 7/36 Bare Copper	0.047" nom.
Insulation:	0.008" Wall FLEXGUARD*	0.063" nom.
Pairing	8 conductors into 4 pairs @ 2.50" LHL.	
Cable:	4 pairs @ 4.00" LHL, aluminum/polypro (foil in) & # 22 7/30 TC drain wire.	0.357" nom.
Jacket:	0.010" Wall PVDF – Natural -Plenum ripcord under jacket.	0.277" +/- 0.014"
Print Legend:	<i>CAROL (R) 18 AWG -- C3364 -- 60C E60233-8 CL2P OR CMP(UL)C(UL) -- MADE IN USA DATE CODE (PRINT EVERY 2 FT)</i>	

B. INDUSTRY APPROVALS

National Electrical Code UL Standard 13	Article 725 Type CL2P
National Electrical Code UL Standard 444	Article 800 Type CMP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	150 Vrms (CL2P); 300 Vrms (CMP)
CONDUCTOR D.C. RESISTANCE:	5.6 Ohms/1000 ft. nom. @ 20C

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black & Yellow
2	Red & Purple
3	Dark Blue & Brown
4	Orange & Dark Green

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.