

Part Number: C4066A

Revision Level: 3

Date: 7/16/2007

6C 22 7/30 TC SR-PVC PVC

COMMUNICATION CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#22 AWG 7/30 Tinned Copper	0.030" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.050" nom.
Cable:	6 conductors @ 2.50" LHL	0.154" nom.
Jacket:	0.032" Wall Polyvinyl Chloride	0.218" +/- 0.011"
Print Legend:	<i>CAROL (R) 22 AWG -- C4066A -- 75C E111240-8 CM (UL) C (UL) OR AWM STYLE 2464 --- CSA LL69381 CMG -- MADE IN USA (DATE CODE)</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	24.5 pF/ft @ 1kHz nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	Red
3	White
4	Lt. Green
5	Lt. Brown
6	Lt. Blue