

Part Number: C4067A

Revision Level: 4

Date: 7/16/2007

12C 22 7/30 TC SR-PVC PVC

COMMUNICATION CABLE

A. CONSTRUCTION

Conductor:	#22 AWG 7/30 Tinned Copper	0.030" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.050" nom.
Cable:	12 conductors @ 2.50" LHL with mylar wrap	0.212 nom.
Jacket:	0.032" Wall Polyvinyl Chloride	0.276" +/- 0.014"
Print Legend:	<i>CAROL (R) 22 AWG -- C4067A -- 75C E111240-8 CM (UL) C (UL) OR AWM STYLE 2464 --- CSA LL69381 CMG -- MADE IN USA (DATE CODE)</i>	

DIAMETERS

B. INDUSTRY APPROVALS

National Electric Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V _{rms}
CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	24.5 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black	11	Pink
2	Red	12	Tan
3	White		
4	Lt. Green		
5	Lt. Brown		
6	Lt. Blue		
7	Orange		
8	Yellow		
9	Purple		
10	Gray		