

Part Number: C6351A

Revision Level: 7

Date: 7/20/2007

2C 20 7/28 TC PVC PVC

COMMUNICATION CABLE

A. CONSTRUCTION

Conductor: #20 AWG 7/28 Tinned Copper
 Insulation: 0.016" Wall Polyvinyl Chloride
 Cable: 2 conductors
 Jacket: 0.025" Wall Polyvinyl Chloride
 Print Legend: *CAROL (R) 20 AWG -- C6351A -- 75C E111240-8 CM (UL) C (UL) --- CSA LL69381 CMG -- MADE IN USA (DATE CODE)*

DIAMETERS

0.037" nom.
 0.069" nom.
 0.142" nom.
 0.192" +/- 0.01"

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V _{rms}
CONDUCTOR D.C. RESISTANCE:	10.3 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	28 pF/ft @ 1kHz nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	White