

Part Number: E1052S

Revision Date: 1/17/2013

2C 14 AWG (19/.0147)BC SR-PVC, PVC**SOUND / ALARM AND SECURITY CABLE****A. CONSTRUCTION****DIAMETERS**

Conductor: #14 AWG 19/.0147 Bare Copper .071" Nom
Insulation: .010" Wall, Semi-Rigid Polyvinyl Chloride (SR-PVC) .091" Nom
Cable Core: 2C with a 8.00" LHL
Jacket: .015" Wall, Polyvinyl Chloride (PVC) .212" Nom
-Ripcord under jacket
Print Legend: **CAROL (R) 14 AWG -- E1052S -- 75C E60233-8 (UL) CL3R -- ROHS --
MADE IN USA (DATE CODE) (SEQUENTIAL FOOTAGE)**

B. INDUSTRY APPROVALS

National Electrical Code Article 725
UL Standard 13 Type CL3R

C. ELECTRICAL PROPERTIES

Temperature: -20°C to +75°C
Suggested Working Voltage: 300V Max
Conductor DCR: 2.65 Ohms/1000 ft max
Mutual Capacitance: 35.5 pF/ft. @ 1 kHz (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____

Date: _____