


M9A029 Fiber - Tight Buffer Breakout Cables (2.5 mm subunits)-Plenum (OFNP)



For more Information
please call

1-800-Belden1

Description:

FiberExpress Optical Fiber Breakout Cables are designed for low to medium fiber count in-building, harsh-environment installations. Breakout or fanout cables offer a high degree of flexibility for backbone and horizontal applications.

Physical Characteristics (Overall)

Fiber Type:	50/125/900 Micron
Number of Fibers:	2
Core Diameter:	50 +/- 2.5
Core Non-Circularity:	5% Maximum
Clad Diameter:	125 +/- 2
Clad Non-Circularity:	1% Maximum
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245 +/- 10
Secondary Coating Material:	FA - Flamarrest®
Secondary Coating Diameter:	900 +/- 50
Breakout Element Diameter:	.098
Breakout Element Material:	Plenum Grade PVC - Polyvinyl Chloride

Buffer Tube Color Code Chart:

Number	Color
1	Blue
2	Orange

Core-clad Offset:	1.5 Microns Maximum
-------------------	---------------------

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
Plenum Grade PVC - Polyvinyl Chloride

Outer Jacket Color:	Orange
---------------------	--------

Strength Member

Strength Member Material:	Aramid Yarn
---------------------------	-------------

Overall Cabling

Overall Nominal Diameter:	0.271 in.
---------------------------	-----------

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +80°C
Operating Temperature Range:	-20°C To +70°C
Bulk Cable Weight:	26 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	4.100 in.
Min. Bend Radius for Long Term Application:	2.700 in.
Crush Resistance:	EIA-455-41, 2000 N/cm
Impact Resistance:	EIA-455-25, 2000 Impacts w/1.6 N-m

M9A029 Fiber - Tight Buffer Breakout Cables (2.5 mm subunits)-Plenum (OFNP)

Cyclic Flexing:	EIA-455-104 2000 Cycles min.
Max. Load for Installation:	180 lbs.
Max. Load for Long Term Application:	65 lbs.
Proof Test:	100 kpsi

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	OFNP
CEC/C(UL) Specification:	OFN
IEEE Specification:	802.3Z

Flame Test

UL Flame Test:	NFPA 262
C(UL) Flame Test:	FT6

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Sunlight Resistance:	No

Plenum/Non-Plenum

Plenum (Y/N):	Yes
----------------------	-----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.5 dB/km
Maximum Attenuation @ 1300nm:	1.25 dB/km
Point Loss @ 850nm & 1300nm:	.2
Minimum Bandwidth @ 850nm:	500 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Refractive Index @ 850nm:	1.483
Refractive Index @ 1300nm:	1.479
Numerical Aperature:	.200
Maximum Gigabit Ethernet Length @ 850nm:	600
Maximum Gigabit Ethernet Length @ 1300nm:	600

Notes (Overall)

Notes: Note: Outdoor installation must be in conduit or protected from UV exposure.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 4 Revision Date: 05-14-2007

© 2010 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

M9A029 Fiber - Tight Buffer Breakout Cables (2.5 mm subunits)-Plenum (OFNP)